

## XTR PRO HEAVY DUTY RECOVERY SYSTEM - DUAL VOLTAGE

## Features:

- 1/2 oil-less AC compressor for fast recovery of all refrigerants including R32 and R1234yf.
- · UL listed ignition protected switches and circuit breaker.
- Low pressure switch stops recovery above ambient pressure for leaking systems to prevent pulling air into recovery cylinders.
- Low pressure bypass for recovery of leak-free systems. Valve control for easy changeover from liquid to vapor to purge.
- Integrated self purge function for quick change from one refrigerant to another.
- · Turbo fan-forced cooling and built-in condenser.
- · Automatic low pressure unit shut off.
- · Heavy duty blow moulded case designed for easy carrying.
- · Dual Voltage Recovery 110v or 240v.
- 1 year factory warranty.
- Designed and manufactured in Australia.



## True Multi-Purpose Recovery Including A2L/R32 Flammable Refrigerants

The original XTR was one of the first high performance recovery units that combined fast recovery with a fan powered condenser. The latest XTR PRO A2L has lived up to its reputation as a heavy duty work horse for recovery of a wide range of refrigerants in the harshest conditions with A2L compliance.

The XTR PRO is specifically designed for heavy duty recovery of new lower GWP refrigerants including R-32 as well as the most common CFC, HFC and HFO refrigerants, including R-22, R-404A, and R-410A. The unique "low pressure over-ride" and hard wired five meter power cord comply with the leading safety requirements.

JAVAC were early pioneers in refrigeration recovery and are the only Australian manufacturers of HVAC/R recovery equipment on the market today. Buy quality, buy JAVAC. A full range of HVAC/R products is available for service professionals.

Calculated Recovery Ratings								
	Kg/min			Kg/hour				
	Vapour	Push/Pull	Liquid	Vapour	Push/Pull	Liquid		
R-22	0.24	6.18	1.55	14	371	93		
R-32	0.15	5.07	1.27	9	304	76		
R404A	0.42	5.44	1.37	25	326	82		
R410A	0.25	5.50	1.80	15	330	108		
R407C	0.25	4.43	1.49	15	226	89		



## **Specifications:**

Weight	14.1 kg		
Size	L 420mm		
	W 290 mm		
	H 420mm		
Connections	1/4 SAE		
HP Cut Out	550 psi		
Operating Temp	-5°C to 60°C		
Noise Level	72 dba		

Warranty 1 Year Warranty

Part #	Description
XTR-PRO	Refrigerant Recovery Unit With Condenser





