



# Pipe Support

IN  
STORE  
TODAY

## 3 Pipe Clips



- Fast fix direct to M8 or M10 studding
- Perfect for VRV / VRF / multi pipework systems
- Fits insulated pipe
- Wide arms for greater pipe support
- Corrosion resistant
- -40°C to 1000°C temperature range
- Meets fire regulations
- Powder coated mild steel construction
- Max. per clip: 3kg load, 1.2m distance apart

SIZING OPTIONS				
Description	Pipe groups from	Pipe groups to	Part No.	Pack Qty
1	3/8" 5/8" 3/4"	1/2" 3/4" 1"	B6361	5
2	1/2" 1 1/8" 3/4"	5/8" 1" 1 1/8"	B6362	5
3	5/8" 1 1/8" 1 1/8"	3/4" 1 3/8" 1 1/8"	B6363	5
4	7/8" 1 3/8" 1 1/8"	3/4" 1 5/8" 1 3/8"	B6364	5

\* Approximate pipe sizes (allowing for 13mm insulation)

## Griplocks



- Maximum installation versatility
- Perfect for multi stage & HVAC/R line sets
- Fits insulated pipe
- Wide arms for greater pipe support
- -40°C to 1000°C temperature range
- Meets fire regulations
- Zinc passivated mild steel construction
- Max. per clip: 3kg load, 1.2m distance apart

SIZING OPTIONS						
Description	Liquid*	Gas*	Width (mm)	Height (mm)	Part No.	Pack Qty
Size 1	1/4"	1/2"	54	30	B6186	10
Size 2	3/8"	5/8"	60	32	B6187	10
Size 3	1/2"	7/8"	67	37	B6188	10
Size 4	5/8"	1 1/8"	80	46	B6189	10

\* Approximate pipe sizes (allowing for 10mm insulation)

## Metal Hangers



- Fast fix direct to M8 or M10 studding
- Ideal for HVAC line set pairs
- Fits insulated pipe
- Corrosion resistant
- -40°C to 1000°C temperature range
- Meets fire regulations
- Zinc passivated mild steel construction
- Max. per clip: 3kg load, 1.2m distance apart

SIZING OPTIONS				
Description	Liquid*	Gas*	Part No.	Pack Qty
2	3/8"	5/8"	B6492	10
3	1/2"	7/8"	B6493	10
4	5/8"	1 1/8"	B6494	10

\* Approximate pipe sizes (allowing for insulation)

## Plastic Hanger



- Easy installation
- Fits on both M8 and M10 studding
- Avoids the need for cable tray
- Adjustable clipping mechanism

SIZING OPTIONS					
Description	Liquid*	Gas*	Rod Fitting Size	Part No.	Pack Qty
P2	3/8"	5/8"	8-10mm drop	B6543	5
P3	1/2"	7/8"	8-10mm drop	B6544	5
P4	5/8"	1 1/8"	8-10mm drop	B6545	5

\* Approximate pipe sizes (allowing for insulation)

## Pinch Clip



- Pinch Clip locates quickly to M8 and M10 studding
- Robust metal construction
- Snap shut lid secures pipe set
- Quick and easy pipe installation
- Wide metal construction for greater pipe support
- Can also be used for surface mount
- Ideal for when you need to meet fire regulations

SIZING OPTIONS				
Description	Liquid*	Gas*	Part No.	Pack Qty
2	3/8"	5/8"	B6561	10
3	1/2"	7/8"	B6562	10
4	5/8"	1 1/8"	B6563	10

\* Approximate pipe sizes (allowing for insulation)



T: +61 (8) 8186 4666  
E: sales@aspenspumps.com.au  
aspenspumps.com.au

## Channel Clips



- Fast twist and clip fixing
- Fits 40 x 40mm & 40 x 20mm channel
- Vertical and horizontal fitting
- -40°C to 70°C temperature range
- Nylon construction
- Max. per clip: 3kg load, 1.2m distance apart
- Fits metric and imperial sizes
- Unique lockable ratchet design
- Fits insulated and uninsulated pipe

SIZING OPTIONS						
Size	6mm	9mm	Lagging 13mm	19mm	Part No.	Pack Qty
6mm (1/4")					B6842	10
10mm (3/8")					B6844	10
13mm (1/2")					B6843	10
16mm (5/8")					B6845	10
19mm (3/4")	1/4"				B6846	10
22mm (7/8")	3/8"				B6847	10
25mm (1")	1/2"	1/4"			B6848	10
28mm (1 1/8")	5/8"	3/8"			B6849	10
32mm (1 1/4")	3/4" 7/8"	1/2" 5/8"	1/4"		B6850	10
35mm (1 3/8")		3/4"	3/8" 1/2"		B6851	10
38mm (1 1/2")	1 1/8"	7/8"	5/8"		B6852	10
41mm (1 5/8")	1 3/8"	1 1/8"	3/4" 7/8"	1/4" 3/8"	B6853	10
50mm (2")				1/2"	B6854	10
55mm (2 1/8")	1 5/8"	1 3/8" 1 5/8"	1 1/8" 1 3/8"	5/8" 3/4" 7/8"	B6855	10

## M10 Stud Clips



- Fast fix direct to studding
- Easy to adjust and relocate
- Fits metric and imperial sizes
- Fits insulated and uninsulated pipe
- -40°C to 70°C temperature range
- Nylon construction
- Max. per clip: 3kg load, 1.2m distance apart

SIZING OPTIONS						
Size	6mm	9mm	Lagging 13mm	19mm	Part No.	Pack Qty
1/4"					B6814	10
3/8"					B6816	10
1/2"					B6815	10
5/8"					B6817	10
3/4"	1/4"				B6818	10
7/8"	3/8"				B6819	10
1"	1/2"	1/4"			B6820	10
1 1/8"	5/8"	3/8"			B6821	10
1 1/4"	3/4" 7/8"	1/2" 5/8"			B6822	10
1 3/8"		3/4"	3/8" 1/2"		B6823	10
1 1/2"	1 1/8"	7/8"	5/8"		B6824	10
1 5/8"	1 3/8"	1 1/8"	3/4" 7/8"	1/4" 3/8"	B6825	10
2"				1/2"	B6826	10
2 1/8"	1 5/8"	1 3/8" 1 5/8"	1 1/8" 1 3/8"	5/8" 3/4" 7/8"	B6827	10

## Insulclamps



- Quick fit with locking nuts
- Fits 40 x 40mm & 40 x 20mm channel
- Fits imperial sizes
- Insulates against heat loss and reduces vibration
- Perfect for Big Foot systems
- 130°C rubber cushion / 1000°C bracket temperature range
- Meets fire regulations
- Zinc passivated steel with thermo rubber cushion construction
- Max. per clip: 3kg load, 1.2m distance apart

SIZING OPTIONS				
Size	Max. Unsupported Span (m)	Height Above Channel (mm)	Part No.	Pack Qty
1/4"	1.2	32	B6268	10
3/8"	1.2	35	B6274	10
1/2"	1.2	38	B6267	10
5/8"	1.2	41	B6276	10
3/4"	1.2	44	B6273	10
7/8"	1.2	47	B6277	10
1 1/8"	1.2	54	B6264	10
1 3/8"	1.2	60	B6265	10
1 5/8"	1.2	76	B6266	10
2 1/8"	1.2	92	B6269	5
2 5/8"	1.2	98	B6270	5
3 1/8"	1.2	117	B6271	5
3 5/8"	1.2	130	B6272	5
4 1/8"	1.2	143	B6275	5

## Quick Positioning Clip



- Easy installation into 40mm x 40mm and 40mm x 20mm channel
- External diameter matches diameter of pipes with 9mm insulation
- Excellent resistance to oil
- Helps dampen noise and vibrations

SIZING OPTIONS				
Size	Max. Unsupported Span (m)	Height Above Channel (mm)	Part No.	Pack Qty
1/4"	1.2	21	B6445	10
3/8"	1.2	24	B6447	10
1/2"	1.2	27	B6444	10
5/8"	1.2	31	B6448	10
3/4"	1.2	34	B6446	10
7/8"	1.2	37	B6449	10
1 1/8"	1.2	43	B6442	10
1 3/8"	1.2	50	B6443	10
1 5/8"	1.2	56	B6538	10